

MicroPOS NBP-55

PROFESIONALNI PAMETNI RUČNI TERMINAL

MicroPOS

NBP-55

- Zaslón 4.0 inča
- Android 10.0 system
- 4G full Netcom



Android



4G



WIFI



Bluetooth



1D barcode



2D barcode



SIM



NFC



Camera



GPS



PARAMETRI PROIZVODA

Performanse

Quad core

Procesor Cortex-A53 Quad core 64 bit 2.0 GHz high performance processor

RAM+ROM 2GB+16GB podržava do 4GB+64GB

Proširenje memorije Micro SD(TF) podržava do 128GB

Sustav Android 10.0

Podatkovna komunikacija

WLAN Dual-band 2.4GHz / 5GHz,
Podržava protokole IEEE 802 a/b/g/n/ac

WWAN 2G GSM (850/900/1800/1900MHz)
3G WCDMA (850/900/1900/2100MHz)
4G FDD:B1/B3/B4/B7/B8/B12/B20
TDD:B38/B39/B40/B41

Bluetooth Podržava Bluetooth 5.0+BLE
Prijenos do udaljenosti od 5-10 metara

GNSS Podržava Gps, Galileo, Glonass, Beidou

Fizički parametri

Dimenzije 201.8mm×72mm×140mm (uključujući ručku)

Težina <750g
(Ovisi o konfiguraciji uređaja)

Zaslona 4.0 ", u boji, rezolucija 480×800

Osjetljiv na dodir Podržava više točaka dodira

Kapacitet baterije Punjiva, skidljiva polimerska baterija (7.6V 3750mah)
Na čekanju >350 sati
U radu >12 sati
Trajanje punjenja >3h sa standardnim adapterom i podatkovnim kabelom

Utori za kartice Kartice NANO SIM x2, TF x1 (izborno PSAM), POGO Pin x1

Sučelje za komunikaciju Type-C 2.0 USB x 1, podržava funkciju OTG

Zvuk Zvučnik (mono), mikroskop, slušalica

Tipkovnica 38 gumenih tipki, lijevi gumb x1, desni gumb x1

Senzori Senzor gravitacije, svjetla, udaljenosti, vibro motor

Dohvat podataka

Skeniranje barkoda (izborno)

2D skeniranje Honeywell N5703 Zebra SE5500

1D Simboli Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, China post 25, ISBN/ISSN, Code93, UCC/EAN-128, GS1 Databar, HIBC, etc.

2D Simboli PDF417, Micro PDF417, GS1 Composite, Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Hanxin Code, etc.

Kamera (Standardno)

Stražnja kamera 800W pixel HD
Podržava auto fokus, bljeskalicu, kompenzaciju trešnje, makro fotografiju

Prednja kamera 500W pixel, u boji

NFC (izborno)

Frekvencija 13.56MHz

Protokol Podržava ISO14443A/B, 15693 agreement

Udaljenost 2cm-5cm

Jezik/način nosa

Ulaz

Jezik Pojednostavljeni kineski, tradicionalni kineski, engleski, korejski, japanski, malajski itd.

Okolina

Radna temperatura -20°C - 55°C

Temperatura za skladištenje -40°C - 70°C

Vlaga okoline 5%--95% relativne vlage (bez kondenzacije)

Otpornost na pad Sa 6 strana, pad s visine od 1.2 metra na mramor pri radnoj temperaturi

Otpornost na kotrljanje Izdrži Kotrljanje 0.5m sa 6 strana

Zaštita IP66

Pribor

Standardno Adapter, podatkovni kabel, zaštitna folija, priručnik

CENTRALNI SERVIS:

Microline d.o.o.

www.microline.hr

micropos@microline.hr

PRODAJNI PREDSTAVNIK:

MicroPOS

