

MicroPOS SLK-TS500 - linija POS printera
prikladna za potrebe aplikacija na
prodajnim mjestima i trgovinama.

MicroPOS

SLK-TS500

Termalni POS printer

- Dostupna širina papira 58 mm/80 mm/82.5 mm
- Funkcija IAP podržava ažuriranje internog programa za 5 sekundi. Održavanje printera je jednostavno.
- Pouzdan rezač s pametnim kodom koji onemogućava gužvanje papira u rezaču.
- Mehanizam s metalnom konstrukcijom



Supermarket



Trgovački centar



Ugostiteljstvo



Banka



MALOPRODAJA



DNEVNI IZVJEŠTAJI



UGOSTITELJSTVO



ULAZNICE



KUPONI




www.micropos.biz



MicroPOS SLK-TS500

Termalni POS printer



Ispis	
Način ispisa	Izravni termalni
Širina papira	58/80/83±0.5 mm
Širina ispisa	72 mm/76 mm/80 mm/64 mm/48 mm/52 mm
Veličina stupca	576 točaka/liniji (podesivo naredbom)
Brzina ispisa	300 mm/s maks.
Sučelje	USB+LAN/USB+Serijsko (izborno: Wifi+Bluetooth)
Prored	3.75 mm (podesivo naredbom)
Broj stupaca	papir 80 mm: Font A - 42 ili 48 stupaca/Font B - 56 ili 64 stupca/ kineski, tradicionalni kineski - 21 ili 24 stupca
Veličina znakova	ANK, Font A:1.5x3.0 mm (12x24 točke) Font B:1.1x2.1 mm (9x17 točaka) kineski, tradicionalni kineski: 3.0x3.0 mm (24x24 točke)
Rezač	
Automatski rezač	Djelomično
Znakovi bar koda	
Prošireni skup znakova	PC347(standardni europski)/Katakana/PC850(višejezični)/PC860 (portugalski)/ PC863(kanadski francuski)/PC865(nordijski)/zapadno europski/grčki/ hebrejski/ istočno europski/iranski/WPC1252/ PC866(ćirilica#2)/PC852(Latin2)/PC858/ iranski II/litvanski/ arapski/PT151(1251)
Vrsta bar koda	UPC-A/UPC-E/JAN13(EAN13)/CIDE39/UTF/CODABAR/ CODE93/CODE128
Barkod 2D	QR CIDE/PDF417
Ulazni međuspremnik	20048 Kb
Memorija NV flash	256 Kb
Napajanje	
Adapter za napajanje	Ulaz: izmjenično 100-240 V, 50-60 Hz Izlaz: istosmjerno 24 V/2.5 A
Ulaz printera	Istosmjerno 24 V/2.5 A
Izlaz ladice za novac	Istosmjerno 24 V/1 A
Fizičke karakteristike	
Težina	1.115 kg
Dimenzije	133x126x130 mm (D*Š*V)
Uvjeti okruženja	
Radno okruženje	0~45°C, 10~80% relativne vlage
Okruženje za skladištenje	-10~60°C, 10~90% relativne vlage (bez kondenzacije)
Pouzdanost	
Trajanje rezača	2 milijuna rezova
Trajanje glave za ispis	150 km
Software	
Upravljački program	Windows/JPOS/OPOS/Linux/Android/Mac
Uslužni programi	Windows i Linus program za ispitivanje
SDK	iOS/Android/Windows

CENTRALNI SERVIS:
Microline d.o.o.
www.microline.hr
micropos@microline.hr

PRODAJNI PREDSTAVNIK:

MicroPOS

